



## 2025 A Class Rules

## 2025 A Class Rules

All drivers, owners, and crew persons are responsible to follow all the Safety rules, and track rules of Delta Speedway. Any person violating those rules will be subject to suspension, an expulsion from the facilities. This is at the sole discretion of Delta Speedway and its appointed officials.

**Disclaimer:** All rules may be changed/modified/adjusted as needed by Delta Speedway. Rules are designed and enforced to keep competition equal and safe.

**Age:** Minimum age is thirteen (13) years old, or twelve (12) years old with at least two (2) years of prior racing experience in the micro/mini sprints. (Subject to Head Official/Promoter discretion)

**Fuel:** Methanol only. No additives allowed, i.e. Power Mist, propylene oxide, nitro methane, etc. No M5.

**Weight:** The minimum weight of a car and driver for the A Class is 750 lbs. All cars must meet weight requirement using scales provided by Delta Speedway. Cars must go directly to scales as directed by racing officials. Any driver that fails to go directly to the scales will be automatically disqualified.

**Tire Rule:** All 4 corners, Hoosier Tires are mandatory in all classes. Right Rear Tire: All Restricted cars must use the Hoosier D25, or harder. Grooving and siping will be allowed. No doping is allowed. There is zero tolerance on doping. Suspension of car and driver will result in the event of doping or chemical alteration of any tire.

- Doping is defined as the chemical alteration of any Hoosier tire from its factory condition. Doping is explicitly PROHIBITED. Chemicals, sprays, soaking, bathing, wiping, rubbing, massaging, baking, needling or any act of applying a foreign substance to either the INTERIOR surface of the tire or the EXTERIOR surface of the tire will NOT be allowed. Injecting chemicals through bleeders or valve stems is explicitly prohibited.
- The head technical inspector is given the right to determine altering based on sensory SIGHT (the act of doing) or SMELL (the odor of chemicals within the rubber of a tire not conducive with the factory form).

**Transmission:** All gears must be in transmission. Transmission must be stock functional and operating.

**Top wing:** Cars must run a max 10 square-foot fixed wing. No mechanical, electrical or hydraulic adjustments are allowed in the cockpit area, for the wing or any other part of the car. Wing center section must be 48" wide x 30" deep. Left side board must be 24" x 48". Right side board must be 18" x 48". Side boards must be 90 degrees to the center section. Wings must be mounted parallel with cage. Top wings are mandatory to enter a night's event.

**Nose wing:** Nose wings cannot exceed 18" x 24". Side boards are not to exceed 8.5" tall and 21" long.

**Numbers:** All cars must have legible numbers painted in contrasting colors on both sides of car and the nose. Minimum height of numbers is 8" on the nose wing, 10" on each side of the tail and 12" on the top wing. Numbers must be separated from advertising so they will be readable. It is recommended that cars have a 12" number on top of the wing facing the front of the car.

**Engine Rules:** All engines must be available to the general public, from a known manufacturer, for at least two (2) years prior to use in either restricted class. No internal engine modifications allowed, i.e. ported heads, lightened cranks, lightened transmissions. All Restricted cars must run a 4-stroke, 4-cylinder, 600cc engine. All engines must run the stock stroke, stock bore, and stock cams. No aftermarket cam sprockets. Manual cam chain tensioner is allowed. Aftermarket valve adjustment shims and valve spring shims are allowed. Must run stock valves and springs. Cylinder head deck cleanup is allowed (flat mill only, no angle milling), maximum from stock is .010 and or 10/1000 of an inch. A stock head will be used for reference. Deck clearance of piston to be -0.002 or greater. The cars must be self-starting, and the flywheel attached to the motor. Engine must be run as it came from the factory, with the internal charging unit and stator. Voltage will be checked at the battery and stator. Visual inspection of the flywheel/stator will be performed if needed. Stock ECU, FuelTech FT550, PE3-IG2 and PE3-8400 Engine control units are permitted for use with carburetors and Stock Fuel Injection. Aftermarket airboxes and headers are allowed. Motors may run a windage tray & or modified oil pan. No traction control devices allowed.

**Exhaust:** All cars must have a muffler mounted on the header. See General Rules (3.38)

**Carburetors:** Carburetors may have metering rods, jets and springs changed to tune the fuel curve to match the car's requirements. Carburetors must be stock, no non O.E.M. carburetors allowed. Motors that use carburetors may run aftermarket boots, so you may run carburetors on the newer style motors that came from the factory with fuel injection. There will be a 2 1/8 inch maximum from the bottom of the billet adapter to the top of the rubber boot. We will continue to monitor boots as well as inside diameters for alterations. Carburetor adapter bottom dimension must be the same as stock O.E.M. intake port opening. Adapter must have a straight flow from the carburetor to the head with the unaltered mandatory King racing products 3/4 plate in place. O.D. of carburetor adapter must allow rubber boot to fit tight as per original design. No funneling of rubber boot allowed. All Restricted cars will be checked for intake leaks, and any car with an intake leak will be disqualified. Manufacturer's engine equipped with factory fuel injection may run a prior year's carburetor.

**Fuel Injection:** Stock Electronic fuel injection systems with OEM throttle bodies will be allowed. Fuel injection system must be OEM to engine make (like engine/like year). No aftermarket throttle bodies are allowed (i.e. billet, castings, etc). Electronic or Mechanical Injectors with a mechanical fuel pump with stock OEM throttle bodies are allowed. OEM Honda, Yamaha, Kawasaki, Suzuki motors that run stock fuel injection must use the stock boot that came with the fuel injection system, as it came from the factory.

**Velocity Stacks:** Aftermarket stock length aluminum Joe's Racing Products velocity stacks are allowed as well as stock plastic velocity stacks. Short velocity stacks are not allowed.

**Driver Compartment Adjustments:** NO cockpit adjustable shocks allowed and No adjustable weight jackers allowed. Pan Hard adjuster is allowed, as long as driver can NOT reach the adjuster, while sitting in vehicle. No electronic adjustments of any kind allowed.

**General Rules:** Please read the General Rules & Regulations. All drivers and crew are responsible for knowing and following these rules.

**Protest Rules:** Please reference the Protest Rules (9.02) under General Rules & Regulations. All drivers and crew are responsible for knowing and following these rules.